



Hydraulic Concentrate Control Valve

The standard hydraulic actuated valve assembly consists of a factory assembled and tested quarter turn full port ball valve to which a hydraulic actuator has been attached. The ball valve has a bronze body with 316 stainless steel ball and stem, or is of all stainless steel construction. Valve seats are glass-reinforced TFE. Inlet and outlet threads are female NPT and flanges are ANSI Class 150. All valves are rated 600 psi WOG. Stainless steel flanged valves are rated 285 psi WOG.

The hydraulic actuator is mounted directly to the ball valve using a mounting bracket. The housing of the actuator has a corrosion resistant exterior with a two-part epoxy coating providing extra protection against aggressive environments. The interior has a long life epoxy or of PTFE finish protecting all body parts against wear and corrosion. The hydraulic actuator is equipped with a visual valve position indicator and has the capability for manual override using a free handle, secured to the valve body with a length of chain. Water to drive the valve open is fed to the hydraulic actuator through 1/4-inch to 1/2-inch pipe or tubing. A connection from the sprinkler system is usually made from a normally unpressurized port, such as the water motor alarm line on the alarm or deluge valve to power the hydraulic actuator. The water inlet to the hydraulic actuator is provided with a "Y" strainer and shut-off valve to allow depressurizing and resetting of the valve after use. In the event electric operation is required or preferred, a solenoid release is installed in the water supply line to the actuator, which will, on system actuation, allow water to flow into the actuator body and open the valve.

APPLICATION

The Chemguard hydraulic concentrate control valve is designed for use with either a bladder tank or a balanced pressure proportioning system. The valve is used to automatically open the line supplying foam concentrate to a ratio controller. Except for those valves ordered with an electric solenoid, electrical power is not required for operation, only water pressure from a system that has been activated.

FEATURES

- (6) Six different sizes available.
- Normal operating pressure range is 40 to 120 psi (2.8 to 8.3 bar). (See Note 1)
- Maximum actuator overload pressure 200 psi (10.3 bar). (See Note 1)
- Durable epoxy finish
- Corrosion resistant alloy case
- Actuator has easy stop adjustments at each end of stroke for accurate seating of the ball



CHEM GUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com

ORDERING INFORMATION

Part No.	Description
2005	1" Hydraulic actuated ball valve, bronze threaded valve
2006	1" Hydraulic actuated ball valve, stainless steel flanged valve
3004	1-¼" Hydraulic actuated ball valve, bronze threaded valve
4004	1-½" Hydraulic actuated ball valve, bronze threaded valve
4005	1-½" Hydraulic actuated ball valve, stainless steel flanged valve
5004	2" Hydraulic actuated ball valve, bronze threaded valve
5005	2" Hydraulic actuated ball valve, stainless steel flanged valve
6004	2-½" Hydraulic actuated ball valve, bronze threaded valve
6005	2-½" Hydraulic actuated ball valve, stainless steel flanged valve
7004	3" Hydraulic actuated ball valve, bronze threaded valve
7005	3" Hydraulic actuated ball valve, stainless steel flanged valve

OPTION:

- For solenoid direct mounted on actuator assembly add the following to part number:
S24 for 24V DC solenoid
S120 for 120V AC solenoid
- For solenoid sold separately use part number:
7000 for 24V DC solenoid
7002 for 120V AC solenoid
- For water regulator sold separately use part number:
7001

NOTE 1:

If normal water supply pressure to actuator operating the valve is above 120 psi (8.3 bar), a water regulator (Part Number 7001) is recommended to reduce actuator inlet pressure so that it does not exceed 120 psi (8.3 bar). Excessive water inlet pressure to the actuator can cause damage to the valve stem.

HYDRAULIC CONCENTRATE CONTROL VALVE

Part No.	Valve Size	End Connection	Actuator	Valve Length - A	
				in.	(mm)
2005	1"	Threaded, NPT	059-100	3.37	85.60
2006	1"	SS RF Flanged, (ANSI, 150#)	059-100	5.00	127.00
3004	1-1/4"	Threaded, NPT	059-100	4.00	101.60
4004	1-1/2"	Threaded, NPT	079-100	4.37	111.00
4005	1-1/2"	SS RF Flanged, (ANSI, 150#)	079-100	6.50	165.10
5004	2"	Threaded, NPT	079-100	4.68	118.87
5005	2"	SS RF Flanged, (ANSI, 150#)	079-100	7.00	177.80
6004	2-1/2"	Threaded, NPT	099-100	6.50	165.10
6005	2-1/2"	SS RF Flanged, (ANSI, 150#)	099-100	7.50	190.50
7004	3"	Threaded, NPT	099-100	6.75	171.45
7005	3"	SS RF Flanged, (ANSI, 150#)	099-100	8.00	203.20

Note: Dimensions subject to change without notice.

CHEMGUARD

204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606

www.chemguard.com